



EVPRO2

UHD NDI PTZ CAMERA

The EVERET EVPRO2 is a high quality UHD 4K60 NDI/HDMI/3G-SDI PTZ Camera with 30x Optical Zoom equipped with a professional 1/1.8" SONY CMOS sensor to capture every detail even in low-light conditions.

Features:

- ▶ Capture up to UHD 4K60 with 30x optical zoom
- ▶ Sony STARVIS IMX334LQR 1/1.8 inch 8.42 MP UHD CMOS sensor
- ▶ Superior High Performance Ambarella ISP chipset
- ▶ NDI High-Quality Video with Low-Latency
- ▶ Offers support for both NDI®|HX2 (4K) and NDI®|HX3 (up to FHD)
- ▶ NDI High Quality Video with low latency, compatible with NDI version 5.5
- ▶ Simultaneous Quad Output*;
NDI®|HX, HDMI, UVC USB and 3G-SDI compatible with Blackmagic Design SDI Level-B
- ▶ Power over Ethernet (PoE) support: get video, control and power supply with one CAT5/6 cable
- ▶ Automatic NDI® Tally Support
- ▶ Supplied with functional IR remote controller
- ▶ Flexible mounting options with image flip function, support upside-down installation
- ▶ OSD menu, IP address, streaming resolution and size can be set in OSD menu
- ▶ 3 year warranty

*Simultaneous output in 4K60 mode will consist of NDI®|HX / IP and HDMI or USB and HDMI

Product specifications

Camera		EVPRO2
Sensor	Sony STARVIS IMX334LQR 1/1.8 inch 8.42 MP UHD CMOS sensor	
Color Space	8bit RGB 4:4:4; ISP RAW (12bit)	
Video		
Video Interface	HDMI 2.0 / 3G-SDI* / USB 2.0 (type-c) / RJ45 (IP) *Level A and B	
Video Encoding	H.264/H.265	
Streaming Protocols	NDI® HX2 / NDI® HX3** / RTMP / SRT / RTSP **max resolution 1080p60	
Bitrate control	Variable or Constant	
Video Bitrate	1024Kbps ~ 61440Kbps	
I-Frame Interval	1 - 120	
Audio		
Interface	3.5mm Line-in	
Samplerate	AAC: 16000Hz – 48000Hz LPCM: 11025Hz – 48000Hz	
Bitrate for AAC	32000Kbps – 128000Kbps	
Volume	1-100	
Video format		
HDMI	3840x2160 P60/50/30/25 29.97/ 24/23.98 1920x1080P60/50/30/25/59.94/29.97/24/23.98 1920x1080I60/50/59.94 1280x720P60/50/30/25/59.94/29.97	
3G-SDI	1920x1080P60/50/30/25/59.94/29.97/24/23.98 1920x1080I60/50/59.94 1280x720P60/50/30/25/59.94/29.97	
USB 2.0 (type-C)	NV12: 1024x576P24 800x480P30 YUYV: 1024x576P24 800x480P27 MJPG: 3840x2160P30/25 1920x1080P60/50/30/25 1280x720P60/50 1024x276P60/50; 800x480P60/50 H264 /H265: 3840x2160P60/50/30/25 1920x1080P60/50/30/25 1280x720P60/50 1024x576P60/50 800x480P60/50/30	
NDI® HX3	Main Stream: 1920x1080@15~60 1280x720@15~60 1024x276P60/50 Sub Stream: 640x360@30	

Product specifications

Camera	EVPRO2
NDI® HX2/RTMP/SRT/RTSP	Main Stream: 3840x2160@15~60 1920x1080@15~60 1280x720@15~60 1024x576@15~60 Sub Stream: 640x360@30
Lens	
Optical Zoom	30x
Digital Zoom	4x
Aperture	F1.35(Wide) - F4.6(Tele)
Focal Length	6.91 ~ 214.64 mm
Horizontal Viewing Angle	60° (Wide) - 2°(Tele)
Vertical Viewing Angle	34.14°~1.12°
Diagonal Viewing Angle	67.08°~2.27
PTZ	
Speed by Zoom	ON/OFF
Pan/Tilt rotation range	Pan: -170° ~+170° Tilt: 30°~+90°
Pan/Tilt rotation speed	Pan: 0.1°~80°/s Tilt: 0.1°~60°/s
PTZ Freeze	Yes
Pan & Tilt Speed	5 - 24
Zoom Speed	1 - 7
Presets	IR Remote : 10, WebUI: 128, EVKB200N: 128, Serial: 128
Save AE & WB settings in preset	ON/OFF
Preset Speed Pan & tilt	5 - 24
Preset Speed Zoom	1 - 7

Product specifications

Camera	EVPRO2
Image	
Shutter Speed	1/1 – 1/10000s
Iris	F1.8 - F14
Minimum Object distance	Wide: 1.5m~INF; Tele: 1.5m~INF
Video S/N Ratio	>50dB
Minimum Illumination	0.1 lux
Focus	Auto / Manual / One Push Auto Focus
Gain Level	0-30Db
White Balance Modes	Auto / Manual / Auto Tracking / One Push / Indoor / Outdoor / Colour Temperature
Exposure Modes	Auto / Manual / Shutter Priority / Iris Priority / Brightness Priority
Wide Dynamic Range Level	Levels 1-6
Gamma	Levels 0-8
Anti-Flicker	OFF / 50Hz / 60Hz
3D NR	OFF / Auto / Level 1-4
2D NR	Yes
Image Flip	Yes
Image Mirror	Yes
Back Light Compensation	Yes
Tally Light	Yes

Product specifications

Camera	EVPRO2
Control	
Network (RJ45)	NDI / HTTP / ONVIF / VISCA over IP (TCP&UDP) / HTML5 (WebUI)
Serial	RS232 / RS422 / RS485 / PELCO P/D
IR Remote	Yes
Daisy Chain	Yes, up to 7 cameras
USB	USB2.0 (UVC1.1)
Visca over IP Port	52381
NDI Port	5961
Network	
Default IP	192.168.1.188
Port Speed	1 Gb/s
PoE	POE+(IEEE802.3at)
DHCP	Yes
Multicast	Yes
NDI Discovery Server	Yes
HTTP Port	80
RTSP Port	554
RTSP Encrypt	Yes
General	
Environment	Indoor
Operating Temperature	-10°C~50°C
Operating Humidity	≤80%

Product specifications

Camera	EVPRO2
Power input	DC12V/POE+(IEEE802.3at)
Power Consumption	PoE+ : 10W, DC in: 10W
Dimensions (LxWxH)	205mm×165mm×191.8mm
Weight	2 KG
EAN (EVPRO2 Black)	8720387387250
EAN (EVPRO2W White)	8720387387267



EVERET

Everet Imaging
 Kraanspoor 50
 1033 SE Amsterdam
 The Netherlands

+31(0)20 798 6654
www.everetimaging.com
info@everetimaging.com

twitter: @everetimaging
 facebook: everetimaging

